

node-indri: moving the Indri toolkit to the modern Web stack

Felipe Moraes and Claudia Hauff

Delft University of Technology
{f.moraes,c.hauff}@tudelft.nl

Abstract. We introduce `node-indri`, a Node.js module that acts as a wrapper around the `Indri` toolkit, and thus makes an established IR toolkit accessible to the modern web stack. `node-indri` exposes many of `Indri`'s functionalities and provides direct access to document content and retrieval scores for web development (in contrast to, for instance, the `Pyndri` wrapper). This setup reduces the amount of *glue code* that has to be developed and maintained when researching search interfaces (which today tend to be developed with `React.js`, `Angular.js`, `Vue.js`, etc.). `node-indri` is available at <https://github.com/felipemoraes/node-indri>.

1 Introduction

The information retrieval (IR) field is aided by numerous efficient search engine implementations, both aimed at researchers and industry such as `Indri`, `Lucene`, `Terrier` and `Anserini`. In the data science field, some of these efforts have evolved into frameworks such as `Elasticsearch` and `Terrier-Spark` [1]. Recently, in order to enable data scientists to make use of `Indri` as part of their workflow, Van Gysel et. [2] have made `Indri` accessible to the Python ecosystem.

In this paper, we make `Indri` accessible to the modern web stack. Many modern web applications and frameworks make use of Node.js. A significant advantage of this framework is the single programming language on the client and server-side (JavaScript), which simplifies development and it is highly scalable [3]. In order to design and evaluate web search interfaces, a backend, implemented in Node.js, requires access to a search system. One option is to call `Indri` via system calls. However, the disadvantage of system calls via `shell commands` is the extra layer of communication with the operating system.

Here, we present an alternative, `node-indri`, a `Node.js` module implemented with an easy API for novice IR users. It provides simple `Indri`'s functionalities such as search with relevance feedback and document scoring. More importantly, `node-indri` is implemented in a non-blocking manner (i.e., asynchronous functions). In addition, we discuss `node-indri`'s module features and we compare its efficiency with `Indri` and `Pyndri` using `Aquaint` and `ClueWeb12` with a load of 10K queries. We find that `node-indri` can be efficiently used in modern Web backend development with comparable results to `Indri` and `Pyndri`.

2 The node-indri module

node-indri’s development started with the need to make Indri’s state-of-the-art relevance feedback models accessible to undergraduate students, who (i) tend to have little experience with C++, but are familiar with modern web programming paradigms and (ii) are not IR experts and thus struggle to make sense of Indri’s internals.

2.1 Functionalities

Figure 1 shows the three layers of abstraction of node-indri’s module. Our module exposes Indri features through the **Searcher**, **Reader**, and **Scorer** classes. These classes are implemented in C++ with the help of Native Abstractions for Node.js¹, a series of macros that abstract away the differences between the V8 and libuv API versions (which together form the core of the Node.js framework and are written in C++).




Fig. 1. Overview of node-indri layers of abstractions together and their implementation languages.

Table 1. Overview of the arguments necessary for node-indri’s method calls. Our API is as simple as possible and includes only one method per class. The last argument is always a callback that is executed when the data has been retrieved. In underlined are the required parameters.

<code>Searcher.search</code>	<code>Reader.getDocument</code>	<code>Scorer.scoreDocuments</code>	<code>Scorer.retrieveTopKScores</code>
<u>query</u> , <u>page</u> , <u>results-per-page</u> , <u>feedback-docs</u> , <u>callback</u>	<u>docid</u> , <u>callback</u>	<u>query</u> , <u>docs</u> , <u>callback</u>	<u>query</u> , <u>number-of-results</u> , <u>callback</u>

In Table 1, we show the arguments of node-indri’s three classes. Each class has a single method with arguments that depend on the functionalities exposed from Indri. The last argument is a callback function implementing the error-first pattern. In this manner, node-indri is an asynchronous module, with most

¹ <https://github.com/nodejs/nan>

of these functions assessing lower-level system functionalities through `libuv`. This in turn means that the methods are executed in `Node.js`' thread pool, making `node-indri` naturally parallel.

The models' hyperparameter settings (e.g. μ in the case of language modeling with Dirichlet smoothing) are manually set via a configuration file. We now discuss the goal of each of the three classes `node-indri` makes available to its users in turn:

Searcher This class exposes the functionalities of `Indri`'s `QueryEnvironment` and `RMExpander` classes through the method `search` which returns a list of search results in a paginated manner. When a 'Searcher' object is instantiated, it takes a configuration object as argument (these settings include the retrieval models' hyperparameters and flags of the type of data to return). When a call to 'search()' is made without and no feedback documents are provided as argument, the standard query likelihood model is employed, otherwise RM3 is [4]. Depending on the configuration settings, the returned result list may contain document snippets (as provided by `Indri`'s `SnippetBuilder`), document scores, document text and other metadata.

Reader This class exposes the functionalities of an `Indri` index through the method `getDocument` in order to return a document's meta- and text data.

Scorer This class provides access to the retrieval scores of a list of document via the method `scoreDocuments`. In addition, it provides `retrieveTopKScores` to retrieve the scores and document ids of the top ranked documents for a query.

2.2 Use Cases

We have used `node-indri` as search results provider in the backend of a large-scale collaborative search system, `SearchX` [5]. `SearchX`'s backend supports the inclusion of many IR backends such as Elasticsearch and Bing API calls. In order to include `node-indri` as one of the supported backends, we implemented `Searcher` to provide search results (with or without snippets) in a pagination manner leveraging feedback documents, `Reader` to enable the rendering of a document's content when a user has clicked on it, and `Scorer` to enable our backend to have direct access to documents' scores for reranking purposes (e.g. diversification).

3 Efficiency Analysis

We now present an efficiency analysis of `node-indri`, comparing it with `Indri` and `Pyndri`. Table 2 presents the query execution time of the three toolkits. More concretely, we indexed two standard test corpora—Aquaint and ClueWeb12B—with `Indri` and measured the execution time for 10k queries of the TREC 2017 Million Query track². As retrieval model we fixed language modeling with Dirichlet smoothing; up to 1000 documents were returned per query. We use `Indri`'s

² <https://trec.nist.gov/data/million.query07.html>

`IndriRunQuery` application for this purpose; for `Pyndri` and `node-indri` we implemented scripts to achieve the same behaviour. Specifically, `Pyndri`'s results were obtained with a `Python` script implemented with `multiprocessing`. In `node-indri`, we make use of `Promises.all`. We limit the execution to 20 threads for all three toolkits³.

Our results show that `node-indri` has execution times comparable to `Indri` and `Pyndri`. We can thus use `node-indri` efficiently in modern Web backend development. We find for a small collection such as `Aquaint` (1 million documents), all three tools to report very similar execution times (between 25 and 29 seconds). In contrast, for a larger collection such as `ClueWeb12B` (50 million documents), the execution times differ to some extent: `Indri` takes on average 27 minutes to process 10K queries, while `node-indri` and `Pyndri` take 34 and 37 minutes respectively. This is expected, as both `node-indri` and `Pyndri` have additional overhead due to the frameworks they are built upon.

Table 2. Overview of retrieval efficiency (in seconds) across two corpora. 10K queries from the TREC 2017 Million Queries track were executed 20 times. Reported are the average (standard deviation) execution time of the batches.

	Aquaint	ClueWeb12B
Indri	29s (0.30s)	1645s (20s)
Pyndri	25s (1.22s)	2262s (340s)
node-indri	25s (0.58s)	2058s (338s)

4 Demonstration

At the ECIR demonstration session, we plan to show off how to create a simple `Express.js` REST API using `node-indri` that can be used to search a collection and display it on a web search interface. We will provide one laptop and guide participants using a code editor how to implement the web search application.

5 Conclusions

We have introduced `node-indri`, a `Node.js` module to enable novice users (with a good web development background) to efficiently implement search applications. In this paper, we have described how `node-indri` exposes `Indri`'s functionalities and how it is currently being used in the backend of a large-scale collaborative search system, that has been successfully tested with several hundred users. Furthermore, we compared `node-indri`'s efficiency in the batch setting with `Indri`'s and `Pyndri`'s. Our plan is to maintain and continue developing `node-indri` for the foreseeable future.

Acknowledgements: This work was funded by NWO projects LACrOSSE (612.001.605) and SearchX (639.022.722). The authors would like to thank Harry Scells for his input.

³ Details and benchmark code are included in the Github repository.

References

1. Macdonald, C.: Combining terrier with apache spark to create agile experimental information retrieval pipelines. In: SIGIR. (2018)
2. Van Gysel, C., Kanoulas, E., de Rijke, M.: Pyndri: a python interface to the indri search engine. In: ECIR. (2017)
3. Tilkov, S., Vinoski, S.: Node.js: Using javascript to build high-performance network programs. IEEE Internet Computing (2010)
4. Lavrenko, V., Croft, W.B.: Relevance based language models. In: SIGIR. (2001)
5. Putra, S.R., Moraes, F., Hauff, C.: Searchx: Empowering collaborative search research. In: SIGIR. (2018)